



Best-in-Class Expandable High-Low Bed

DID YOU KNOW? EasyCare's engineered toroidal steel structure is up to 30x stronger than competitors' channel & angle iron models.



SAFE WORKING LOAD: 600 LB

SPECIFICATION SNAPSHOT

Frame Mobility	Roll-in-Low (RIL)
	Roll-any-Height (RAH)
Height from Floor	7" - 30"
Dimensions (W x L)	35" x 80", up to 42" x 88"
Overall Bed Length	84.25" L
Pendant Functions	Back with Comfort Pause, knee, hi-low, Comfort Chair, AutoContour, personalized AutoTransfer, lockout with indicators
Staff Control Functions*	Pendant functions and Gravity Assist, Trendelenburg, reverse Trendelenburg, personalized AutoTransfer Height, function lockout, SafeLight control
Sleep Deck Style	Toroidal steel therapeutic grid
Actuators	4 actuator system
Casters	Heavy-duty 3" diameter
Horizontal Movement	< 1"
Battery Backup	Built-in*
WARRANTY INFORMATION (see user manual)	
Electrical Components	4-year
Bed Frame	15-year
Welds	Lifetime



Connexio® Smart Network Care Management, Simplified

Connexio® smart network enables improved efficiency and delivery of care by empowering operators and clinicians with real time visibility of assets, staff and residents. Ready to connect your EasyCare® and UltraCare® beds?

PATIENT-DRIVEN FIT


Personalized AutoTransfer Height for safer resident-specific mobility.



Unique 30°/45° comfort pauses help to improve sleep, circulation and respiratory therapy adherence.



Adaptable length extensions and width expansions serve more residents.



PERFORMANCE

Hand pendant with integrated hook meets the challenges of institutional care and has back-lit tactile buttons for dark rooms.



Sleep Mode feature saves 80% more power when bed is not in use.



Faster bed movement enables caregivers to react in a moment of need and to reduce fall hazard.



SAFETY

Patented arched leg† offers industry-leading low bed height that mitigates fall injury.



LED SafeLight* provides floor visibility in three soft intensities to safely get out of bed at night.



Height range of 7" to 30" reduces the risk of patient injury and caregiver back strain.



TECHNICAL SPECIFICATIONS

FRAME	
Frame Mobility	Roll-in-Low (RIL), Roll-any-Height (RAH)
Mobility Lock Mechanism	RIL: Large, High-grip Rubber Feet + Locking Casters, RAH: CareLock Dual Foot Pedals
Overall Bed Length	84.25", 88.25", 92.25"
Safe Working Load	600 lb
Product Weight	RIL: 220 lb, RAH: 230 lb
SLEEP DECK	
Height from Floor	7" - 30"
Dimensions (W x L)	35" x 80"
Width Expansion Options	Integrated: 35", 39", 42"; Fixed Width Accessory*: 42"
Length Extension Options	Integrated: 80", 84", 88"; Fixed Length Accessory*: 4", 8"
Angle Range	Back: 0 - 65°, Knee: 0 - 35°
ELECTRICAL	
Power Saving Standby Mode	0.5W at idle
Circuit Protection	Auto Reset Current Sensor
Backup Battery Option*	On-board Charging
ADVANCECARE POSITIONING	
Standard with Backlit Control	Hi-Low, Back, Knee, One-touch Comfort Chair, AutoContour, One-touch Programmable AutoTransfer, Programmable Low Height, Pendant Lockout Access with Indicators
Back Angle and Low Height Pauses	Standard Comfort Pauses (30° and 45°), Low Height Obstruction Reminder
Included with Staff Control	AdvanceCare Staff Control with Function Lockout, Programmable AutoTransfer Height, Programmable Gravity Assist and Trendelenburg/Reverse Trendelenburg, SafeLight Under-bed Light Control*, 3 level programmable
COMPLIANCE	
HBSW Compliant	Bed System
Regulation Compliance	Conforms to IEC 60601-1, 60601-1-2, and 60601-2-52

Specifications may vary due to manufacturing tolerances.

* Sold Separately

† US Patent 6473922

ASSIST DEVICES



F028 Deluxe Assist Handle



F026 Pivoting Assist Handle



F025 Assist Handle



F18 SoftCare Deluxe Assist Device



F14 Assist Device



Trapeze Patient Helper

ACCESSORIES



Multiple Panel Style and Finish Options



Staff Control



LED SafeLight



Built-in Battery Backup



42" Width Expansion



4" / 8" Length Extension

